



Natural Finish Stone Sealer

Water based Impregnating Sealer

Interior & exterior use

For all types of natural and artificial stone, quarry, brick, concrete & paving. Honed, rough cut and polished surfaces.

A natural finish water based impregnating sealer. Minimal change to surface character. Helps protect against staining. Strongly repels water, oil and grease. Allows surface to breathe. Helps reduce efflorescence.

Directions for use

Preparation:

Ensure surface to be treated is completely clean, dry and free from dirt, grime, cement and grout. If necessary, first wash surfaces with a dilute solution of Stone & Tile Intensive Cleaner 1:10 and white pad. Rinse well to remove residues and leave to dry (24hrs).

Rough cut, tumbled, textured or riven surfaces Shake bottle before use. Apply generously and evenly using foam roller or paint brush. On more absorbent surfaces apply further coats at hourly intervals until the surface is fully saturated.

On larger external surfaces and patios apply using a light pressure sprayer.

Honed, smooth and polished surfaces Shake bottle before use. Apply liberally and evenly using a sealant applicator pad, lint free cloth, lamb's wool applicator or sponge. Leave surfaces to dry. Remove any residual sealer if still visible after one hour.

On vertical surfaces apply from the bottom up.

Coverage: M² per coat

	1 LTR	5 LTR
Lower porosity surfaces	15m ²	75m ²
Higher porosity surfaces	7.5m ²	37.5m ²
Polished surfaces	30m ²	150m ²

Aftercare

Interiors: Routinely sweep and wash the floor. Clean walls, floors and work surfaces with ECOPROTEC Natural Stone & Porcelain Aftercare Cleaner.

Exterior: Routinely sweep areas. Wash down with ECOPROTEC Natural Stone & Porcelain Aftercare Cleaner once or twice a year to keep surfaces free from organic stains.

Storage information

Store in a cool, dry, frost-free environment. Store locked up.

Shelf Life – Up to 2 years for un-opened containers.

Other

Dried on over applied sealer can be removed by buffing with micro fibre cloth or rotary machine with buffing pad. If dried on residues are left too long and difficult to buff away; apply a little soapy water and gently scrub with a white emulsifying pad, rinse and leave to dry.

Empty containers are recyclable. Active ingredients are water soluble and inert once cured.

Turn off under-floor heating prior to sealing. If in doubt, test on an inconspicuous area prior to general application. Avoid using strong detergents to wash treated surfaces. On higher porosity materials sufficient sealer should be applied until treated surfaces are fully saturated.

Do not use in temperatures under 5°C or over 25°C. Clean application tools and brushes with water after use.

Health, Safety & Environmental

Contains 2-methylisothiazol-3(2H)-one(2682-20-4). May produce an allergic reaction.

Keep out of reach of children.



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area



Technical Data sheet - Natural Finish Stone Sealer

LTP, Tone Estate, Milverton Road, Wellington, Somerset TA21 0AN