



Wall & Floor Grout Protector

A high-performance water-based impregnating grout sealer. Easy to apply dries to leave a non-film-forming protective barrier on wall and floor grout joints. Allows the grout to breathe and provides excellent resistance to oil, grease and water. Helps with the cleaning and aftercare.

Directions for use

Shake the bottle. Ensure surface to be treated is completely clean, dry. If necessary, first wash the surface with ECOPROTEC Grout Haze & Limescale Remover.

Adjust the nozzle according to the width of spray required. Hold the spray 15-20cm away from the grout joint and apply covering the grout joint. As soon as the grout joint has absorbed the sealer, wipe the surface of the tiles with a micro - fibre cloth. This will remove the excess from the surface of the tile. Leave to dry for 1 hour. On wider deeper joints a second application maybe required.

Treated areas should be dry enough to walk on after about 1 hour but will take 72 hours to become fully resistant. During this time DO NOT cover the surface and wipe up any spills immediately. Do not apply in direct sunlight or in temperatures exceeding 25°C. Always remove residues as instructed. Do not apply if an underfloor heating system is on.

Coverage

Up to 500 linear metres per 500ml depending upon the width of the grout joint and number of coats required.

Aftercare

Floors: Mop routinely with ECOPROTEC Stone & Porcelain Aftercare Cleaner. Walls: Spray and wipe with ECOPROTEC Multipurpose Cleaner.

Storage information

Store in a cool, dry, frost-free environment between +5°C and +25°C. Shelf life can be up to 2 years in the original unopened containers

Health, Safety & Environmental

Contains: 2-METHYLISOTHIAZOL-3(2H)-ONE.

May cause an allergic skin reaction. Keep out of reach of children. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN: Wash with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention.

Warning



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.

